



**Product:** [1868ENH](#) 

Cat 5e Patch Cable, F/UTP, LSZH, 4 Pair, AWG 26, Indoor

## Product Description

Cat. 5e (100MHz), 4-Pair, F/UTP Foil shielded, Work Area Patch Cable, 26 AWG stranded (7x34) bare copper conductors, Polyethylene insulation, Beldfoil® shield, AWG 26 stranded (7x34) tinned copper drainwire, LSZH jacket, RJ-45 compatible

## Technical Specifications

### Product Overview

Suitable Applications:	Work area patch cable; Support current and future Category 5e applications, such as: 1000Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM
Patent:	This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a> .

### Physical Characteristics (Overall)

#### Conductor

Element	AWG	Stranding	Material	No. of Pairs
Individual pair	26	7x34	BC - Bare Copper	4
Conductor Count:				8
Total Number of Pairs:				4

#### Insulation

Element	Type	Material	Nominal Diameter
Individual pair	Dielectric	PE - Polyethylene	0.95 mm
Bonded-Pair:			No

#### Color Chart

Number	Color
Pair 1	Black/Blue & Blue
Pair 2	Black/Orange & Orange
Pair 3	Black/Green & Green
Pair 4	Black/Brown & Brown

#### Cabling

Description
4 pairs twisted together

#### Outer Shield

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Tape	Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	26 (7xAWG34)	Stranded	Under foil
Table Notes:			Aluminum facing inside in contact with drain wire			

#### Outer Jacket

Material	Nominal Diameter	Diameter +/- Tolerance	Max. Diameter	Min. Wall Thickness	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	5.4 mm	0.3 mm	5.9 mm	0.4 mm	0.45 mm

### Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
---------------------------------------	------

Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

## Electrical Characteristics

### Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
145 Ohm/km	4 %	2 %

### Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
160 pF/100m	56 pF/m

### Impedance

Nominal Characteristic Impedance
100 Ohm

### Delay

Max. Delay Skew	Min. Velocity of Propagation
40 ns/100m	60%

### High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	3.2 dB/100m	65.3 dB	62.3 dB	62.1 dB	59.1 dB	64 dB	61 dB	20 dB	40 dB	35 dB
4 MHz	6 dB/100m	56.3 dB	53.3 dB	50.3 dB	47.3 dB	52 dB	49 dB	23 dB	34 dB	23 dB
10 MHz	9.5 dB/100m	50.3 dB	47.3 dB	40.8 dB	37.8 dB	44 dB	41 dB	25 dB	30 dB	15 dB
16 MHz	12.1 dB/100m	47.2 dB	44.2 dB	35.2 dB	32.2 dB	39.9 dB	36.9 dB	25 dB	28 dB	10.9 dB
20 MHz	13.5 dB/100m	45.8 dB	42.8 dB	32.2 dB	29.2 dB	38 dB	35 dB	25 dB	27 dB	9 dB
31.25 MHz	17.1 dB/100m	42.9 dB	39.9 dB	25.8 dB	22.8 dB	34.1 dB	31.5 dB	23.3 dB	25.1 dB	5.5 dB
62.5 MHz	24.8 dB/100m	38.4 dB	35.4 dB	13.6 dB	10.6 dB	28.1 dB	25.1 dB	20.7 dB	22 dB	
100 MHz	32 dB/100m	35.3 dB	32.3 dB	3.3 dB	0.3 dB	24 dB	21 dB	19 dB	20 dB	

Table Notes:	Limits below 4 MHz are for information only. Reference standard: IEC 61156-5
General Electrical Parameters Notes:	Reference standard: ISO/IEC 61156-5
Coupling Attenuation Class:	Type II
Segregation class according EN50174-2:	a

### Transfer Impedance

Frequency [MHz]	Transfer Impedance
1 Mhz	Max. 50 mOhm/m
10 Mhz	Max. 100 mOhm/m
30 Mhz	Max. 200 mOhm/m
100 Mhz	Max. 1000 mOhm/m

Transfer Impedance Class:	Grade 2
---------------------------	---------

### Current

Max. Recommended Current [A]
1.5 Amps per Conductor

### Voltage

Voltage Rating [V]
72 V

## Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

## Mechanical Characteristics

Bulk Cable Weight:	31 kg/km
Max. Pull Tension:	45 N
Min. Bend Radius During Installation:	42 mm
Min Bend Radius During Operation:	21 mm

Standards

ISO/IEC Compliance:	ISO/IEC 11801-1
CENELEC Compliance:	EN 50173-1
Data Category:	Category 5e
ANSI Compliance:	ANSI/TIA 568.2-D (2018)
IEEE Compliance:	PoE: IEEE 802.3bt Type 1, Type 2, Type 3

Applicable Environmental and Other Programs

Environmental Space:	Indoor
----------------------	--------

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1
Burning Load:	395 kJ/m
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3

Part Number

Variants

Item #	Color	Put-Up Type	Length	EAN
1868ENH.00B100	Gray, RAL 7032	Flat Box	100 m	8719605004574
1868ENH.00500	Gray, RAL 7032	Reel	500 m	8719605004567
1868ENH.001000	Gray, RAL 7032	Reel	1,000 m	8719605004550

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system.
--------	----------------------------------------------------------------------------------------------------------------------------------

History

Update and Revision:	Revision Number: 0.274 Revision Date: 11-02-2021
----------------------	--------------------------------------------------

© 2021 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.