



Product: [1888EPE](#)

Cat 7A+ Cable, S/FTP, PE, 4 Pair, AWG 22, Outdoor

Product Description

CAT7A (1200MHz), 4-Pair, S/FTP shielded, Premise Horizontal Cable, 22 AWG solid bare copper conductors, Foam Polyolefin insulation, each pair with Beldfoil® shield, overall tinned copper braid shield (50% coverage), PE jacket

Technical Specifications

Product Overview

Suitable Applications:	Horizontal and building backbone cable; Support current and future Cat. 6a, 7 and 7a applications such as; 10GBase-T (10 Gigabit Ethernet), 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI and ATM; Outdoor
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
22	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Material	Nominal Diameter
PO - Polyolefin (Foam)	1.6 mm

Bonded-Pair:	No
--------------	----

Color Chart

Number	Color
Pair 1	White / Blue
Pair 2	White / Orange
Pair 3	White / Green
Pair 4	White / Brown

Outer Shield Material

Type	Layer	Material	Min. Coverage [%]
Tape	1	Bi-Laminate (Alum+Poly)	
Braid	2	Tinned Copper (TC)	50%

Table Notes:	Aluminium facing outside
--------------	--------------------------

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene	7.8 mm	0.3 mm

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 %

Capacitance

Max. Capacitance Unbalanced Pair to Pair	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Delay

Max. Delay Skew
25 ns/100m

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
1 MHz	2.1 dB/100m
4 MHz	3.7 dB/100m
10 MHz	5.8 dB/100m
16 MHz	7.3 dB/100m
31.2 MHz	10.3 dB/100m
62.5 MHz	14.6 dB/100m
100 MHz	18.5 dB/100m
155 MHz	23.2 dB/100m
250 MHz	29.7 dB/100m
500 MHz	42.8 dB/100m
600 MHz	47.1 dB/100m
1000 MHz	61.9 dB/100m
1200 MHz	68.4 dB/100m

Table Notes:	Limits below 4 MHz are for information only. Values at 1200 MHz are for information only
Coupling Attenuation Class:	Type I
Segregation class according EN50174-2:	d
Transfer Impedance Class:	Grade 1

Current

Max. Recommended Current [A]
1.5 Amps per Conductor

Voltage

Voltage Rating [V]
Max. 72 V DC

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	67 kg/km
Max. Pull Tension:	105 N

Standards

IEC Compliance:	ISO/IEC 11801-1
CPR Euroclass:	Fca
GENELEC Compliance:	EN 50173-1
Data Category:	Category 7A
ANSI Compliance:	ANSI/TIA 568.2-D (2018)
IEEE Compliance:	PoE: IEEE 802.3bt Type 1, Type 2, Type 3, Type 4

Applicable Environmental and Other Programs

Environmental Space:	Outdoor
EU RoHS Compliance Date (yyyy-mm-dd):	2015-05-29

Flammability, LSOH, Toxicity Testing

Burning Load:	1500 kJ/m
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 μ S/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
1888EPE.00500	Black	Reel	500 m	8719605004826
1888EPE.001000	Black	Reel	1,000 m	8719605125187

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system.
--------	--

History

Update and Revision:	Revision Number: 0.152 Revision Date: 09-25-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.