



## NAUSB-W-B

Reversible USB 2.0 gender changer (type A and B), black D-housing

Due to the rising digitisation the interface problems between audio/video networks, IT equipment, MP3 camcorders, etc. increase. A rugged solution is needed.

Neutrik's reversible USB gender changer, mounted in the standardized D-shape housing, and the rugged patch cables solve this problem.

### Features & Benefits

- Ideal for audio networking and integration of computerbased equipment into audio systems
- Optional screen to chassis grounding
- Reversible insert offering type A or B on front or rear end
- IP65 ingress protection in mated condition with NKUSB-\* and SCDP-\* sealing gasket
- USB 2.0 gender changer type A-B (B-A)
- Universally accepted standard D-shape housing

## Technical Information

| Product         |           |
|-----------------|-----------|
| Title           | NAUSB-W-B |
| Connection Type | Adapter   |
| Gender          | female    |

| Mechanical         |                      |
|--------------------|----------------------|
| Wiresize           |                      |
| Mounting direction | Front mounting       |
| Chassis shape      | D                    |
| Lifetime           | > 1000 mating cycles |

| Material        |                         |
|-----------------|-------------------------|
| Contact plating | Au                      |
| Contacts        | Brass (CuZn39Pb3)       |
| Insert          | PBTP 15 % GR            |
| Shell           | Zinc diecast (ZnAl4Cu1) |
| Shell plating   | Black chromium          |

| Environmental       |                        |
|---------------------|------------------------|
| Flammability        | UL 94 V-0              |
| Standard compliance | USB 2.0 specifications |
| Temperature range   | -25 °C to +85 °C       |