Plug-in bridge - FBS 10-6



https://www.phoenixcontact.com/nl/producten/3030271



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, pitch: 6.2 mm, color: red

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Plug-in bridge - FBS 10-6



https://www.phoenixcontact.com/nl/producten/3030271



Technical Data

Prodi	uct	nroi	perties

Number of positions	10
Electrical properties	
Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Connection data

Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal
	blocks.)

Dimensions

Width	60.3 mm
Height	23 mm
Pitch	6.2 mm

Material specifications

Color	red
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Mounting

Mounting type	Plug-in mounting

Phoenix Contact 2021 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT B.V. Hengelder 56 6902 PA Zevenaar Postbus 246 6900 AE Zevenaar (0316) 59 17 20 sales@phoenixcontact.nl