



CLT100F-C20 Loom Tubing, Black, PE, 1" Nom Dia., 100', PK1

CLT100F-C20

The CLT100F-C20 Corrugated Loom Slit Wall Tubing protects cables from impact and abrasion. Features a slit for easy installation onto a bundle of wires or a pre-assembled harness assembly, increasing productivity. Hold in place with cable ties and accessories. Suitable for indoor applications. UL94-HB flammability rating and a maximum temperature rating of 122°F (50°C). Polyethylene. Inside diameter 0.91" (23.2mm). Color Black. 1 per package.

Specifications

Application	Covers wire and cable to protect from abrasion
Note	Slit Wall
Product Type	Corrugated Loom Tubing
Color	Black
Environment	Indoor
Flammability Rating	UL94-HB
Inside Diameter (In.)	0.917
Inside Diameter (mm)	23.29
Material	Polyethylene
Resistance Properties	Provides light crush and impact resistance
Maximum Operating Temperature (°C)	50
Minimum Operating Temperature (°C)	-40
Maximum Operating Temperature (°F)	122
Minimum Operating Temperature (°F)	-40
Nominal Diameter (In.)	1
Nominal Diameter (mm)	25.4
Outer Diameter (In.)	1.114
Outer Diameter (mm)	28.3
Overall Length (ft.)	100
Overall Length (m)	30.5
Standards Met	RoHS Compliant
Part Features	Provides protection for cables. Slitted for easier install onto a bundle of wires or a pre-assembled harness assembly

Packaging Detail

UPC	07498328715
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	2.4780
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000